

➤ INCREASE YOUR SAFETY ON BOARD WITH INNOVATIVE TECHNOLOGY



AIS-SART

SEARCH AND RESCUE TRANSMITTER



www.jotron.com



▶ AIS-SART

GMDSS SEARCH AND RESCUE TRANSMITTER

- Adopted by IMO RES MSC. 256 (84) as an alternative to 9GHz SART

Proved performance:

- Up to 10 nm from a SOLAS ship with AIS class A transponder
- Up to 40 nm from a SAR helicopter (altitude 1000 ft)
- Up to 130 nm from a SAR aircraft (altitude 20000 ft)
- Unique AIS technology contribute to a more effective and less time consuming SAR operation, due to superior position accuracy
- The AIS-SART is detected on both AIS Class A and B
- Small and compact
- Jotron Tron AIS-SART use the same accessories as the Tron SART20 (Bulkhead bracket, pole, life-boat bracket and neoprene protection bag)


SPECIFICATIONS

Weight:	450g (16 oz)
Height:	251 mm (9 7/8')
Material housing:	Glass fiber filled Polycarbonate
Frequency:	161.975 and 162.025 MHz (AIS 1 and 2)
Radiated power:	Minimum 1W ERP (+30 dBm)
Time to GPS fix:	Typically less than 2 min when operated in an area with good satellite coverage.
Signaling:	Broadcasts position message, one burst every minute. Broadcast safety message; "SART ACTIVE"
Position update:	Every minute
Antenna pattern:	Vertical polarization
Antenna height:	Place at least 1m (3.3 ft) above sea/ground level
Indicators:	Transmitter and GPS system operating
Temperature range:	Operating: -20°C to +55°C (-4°F to +131°F) Storage: -30°C to +65°C (-22°F to +149°F)
Battery:	Lithium, non hazardous battery for safe and unrestricted transportation
Operating life:	Minimum 96 hours
Standards:	MSC.246(83), ITU-R M.1371, IEC 61097-14, IEC 60945, SOLAS convention

ACCESSORIES

Brackets:	Bulkhead bracket Lifeboat bracket
For life raft:	Life raft mounting pole Neoprene bag and strengthened lanyard

WARRANTY 5 years



Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

www.jotron.com

CONTACT INFORMATION

Jotron AS
P.O.Box 54
3280 Tjodalynng
Norway
Tel: +47 33 13 97 00
Fax: +47 33 12 67 80
sales@jotron.com

Jotron UK Ltd.
Crosland Park, Off Crowhall
Road Cramlington
Northumberland NE23 1LA,
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd.
19 Loyang Way,
Changi Logistics Centre
Rear Office Block 04-26
Singapore 508724
Tel: +65 65426350
Fax: +65 65429415
sales@jotron.com

Jotron USA, Inc.
10645 Richmond Avenue, Suite 140
Houston, TX 77042
USA
Tel: +1 713 268 1061
Fax: +1 713 268 1062
sales@jotron.com