



# PHONTECH Communication Systems


## SPA 1500 PUBLIC ADDRESS SYSTEM



[www.jotron.com](http://www.jotron.com)

# ▶ SPA 1500

The SPA-1500 system is a standard marine Small Public Address system, especially designed to cover the need for PA and entertainment distribution onboard small and medium size vessels. This system has a very compact design, but comprises much of the functionality of larger systems. The customers may choose between many additional functions/facilities, and thus obtain an almost tailor-made PA system.



- Self supporting rack modules, outer cabinet available.
- Extremely compact design.
- Up to 3 zones selectable in any configuration.
- Up to 3 microphone units, full facility or predefined access.
- Up to 1080W output power. (further expansion optional).
- External paging facility. (from PABX etc.).
- 2 entertainment sources, each distributed to any zone(s).  
Source 1: internal Cassette/CD/radio player,  
Source 2: any external audio program.
- Facility for muting local loudspeaker during paging.
- 6 access priority levels.
- 3 different alarms w/priority. (optional).
- Chime/"ding-dong" generator. (optional).
- Override of volume-controls during paging.
- Alarm light signal activation. (optional).
- Mute of external alarm facility. (optional).



## SPECIFICATIONS

- SPA-1500 and power amplifiers are 19" rack mounting.
- 1510 rack is 6 HE/19" h=338, w=553, d=600mm.
- 1530 rack is 12HE/19" h=604, w=553, d=600mm.
- Power requirement: 24VDC , 110-240VAC with automatic mains failure backup. (option).
- Power consumption: Dependant of amplifiers used.
- Available amplifiers: 120W, 240W, 360W units.
- Related units: Relay unit 9000, Volume controls from 6-100W, Signal lights, PA loudspeakers (100V line).
- Microphone input level: 5mV (typical).
- External paging input/output level: 0dBm (typical).
- External paging activation: NO/NC dry contacts.
- Entertainment input level: 0dbm (typical).
- Amplifiers output level: 100V.
- SPA 1501/1506 control unit, flush or wall (option).
- Noise cancelling gooseneck -, or hand microphone.
- Backlight of switchpanel.
- 1501/1506 dimension: h=144, w=96, d=47mm



**Volume controls**



6W



40W

**Microphone Stations**



1176



0012

**Loudspeakers**



HP-10T



HP-15T



CAR 6T



BF 560T

SPA 1500 is type approved by the following classification societies : CCS, RMRS, RINA



**Agent/Distributor:**

Jotron Phontech AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

[www.jotron.com](http://www.jotron.com)

**CONTACT INFORMATION**

**Jotron Phontech AS**  
 P.O.Box 274  
 3192 Horten  
 Norway  
 Tel: +47 33 08 35 00  
 Fax: +47 33 08 35 01  
[sales@phontech.com](mailto:sales@phontech.com)

**Jotron UK Ltd.**  
 Crosland Park, Off Crowhall  
 Road Cramlington  
 Northumberland NE23 1LA,  
 United Kingdom  
 Tel: +44 (0) 1670 712000  
 Fax: +44 (0) 1670 590265  
[sales@jotron.co.uk](mailto:sales@jotron.co.uk)

**Jotron Asia Pte. Ltd.**  
 19 Loyang Way,  
 Changi Logistics Centre  
 Rear Office Block 04-26  
 Singapore 508724  
 Tel: +65 65426350  
 Fax: +65 65429415  
[sales-asia@jotron-asia.com](mailto:sales-asia@jotron-asia.com)

**Jotron USA, Inc.**  
 10645 Richmond Avenue, Suite 140  
 Houston, TX 77042  
 USA  
 Tel: +1 713 268 1061  
 Fax: +1 713 268 1062  
[contact.us@jotron-usa.com](mailto:contact.us@jotron-usa.com)